

Specialty Gable Vents

RECTANGLE



32"x42"◆

O.D.: 32.4"x 42.6" • Depth: 2.125"
V/A: 265 sq. in. • R/O: 17"x 17"
locking positions: .625, .875, 1.125, 1.375
Item # 00 47 3242 ***

ELONGATED OCTAGON



26"x38"◆

O.D.: 26.4"x 38.1" • Depth: 2.12"
V/A: 158 sq. in. • R/O: 13"x 13"
locking positions: .625, .875, 1.125, 1.375
00 47 2638 ***

32"x47"◆

O.D.: 32.3"x 47" • Depth: 2.12"
V/A: 268 sq. in. • R/O: 17"x 17"
locking positions: .625, .875, 1.125, 1.375
00 47 3247 ***

OCTAGON



40"◆K

O.D.: 38.1" width
Depth: 2.12"
V/A: 239 sq. in.
R/O: 15"x 16"
locking positions: .625, .875, 1.125, 1.375
00 47 0040 ***

HORIZONTAL OVAL



27"x21" Ellipse◆ K

O.D.: 27"x 21" • Depth: 2.175"
V/A: 72 sq. in. • R/O: 8"x 8"
locking positions: .75, 1.00, 1.25, 1.5
00 47 0027 ***

Specialty Gable Vents Available in
White (001) and Paintable (030) only.
Shipped: Metamora, MI
Custom lead times apply

PENTAGON



34"x50" 10/12 Pitch◆

O.D.: 34.4"x 50.4" • Depth: 2.125"
V/A: 260 sq. in. • R/O: 17"x 17"
locking positions: .625, .875, 1.125, 1.375
00 47 3450 ***

26"x39" 10/12 Pitch◆

O.D.: 26.3"x 39.2" • Depth: 2.125"
V/A: 153 sq. in. • R/O: 13"x 13"
locking positions: .625, .875, 1.125, 1.375
00 47 2639 ***

14.5"x74" 4/12 Pitch◆

O.D.: 14.5"x 74" • Depth: 2.5"
V/A: 56 sq. in. • R/O: 8"x 7"
locking positions: .625, .875, 1.125, 1.375
00 47 0404 ***

17"x70.5" 5/12 Pitch◆

O.D.: 16.9"x 70.5" • Depth: 2.5"
V/A: 74 sq. in. • R/O: 8"x 10"
locking positions: .625, .875, 1.125, 1.375
00 47 0505 ***

18"x72.5" 6/12 Pitch◆

O.D.: 18.1"x 72.5" • Depth: 2.125"
V/A: 61 sq. in. • R/O: 8"x 8"
locking positions: .625, .875, 1.125, 1.375
00 47 0605 ***

20.5"x70.5" 7/12 Pitch◆

O.D.: 20.5"x 70.5" • Depth: 2.125"
V/A: 81 sq. in. • R/O: 9"x 9"
locking positions: .625, .875, 1.125, 1.375
00 47 0706 ***

21"x62.5" 8/12 Pitch◆

O.D.: 20.8"x 62.5" • Depth: 2.125"
V/A: 69 sq. in. • R/O: 9"x 9"
locking positions: .625, .875, 1.125, 1.375
00 47 0806 ***

K = Keystones available

Modifications need to be made in the field for a keystone to fit except for the 22" Octagon, 22" Round, and 22"x34" Half Round vents.

◆ = Sonically welded vents

(available in white & Paintable only)

O.D. = Outside Dimensions

(outside of ring to outside of ring)

Depth = Thickness

V/A = Venting Area (square inches)

R/O = Rough Air Opening

DIAMOND



35"x42" 14/12 Pitch◆

O.D.: 35.4"x 41.9" • Depth: 2.125"
V/A: 127 sq. in. • R/O: 12"x 12"
locking positions: .625, .875, 1.125, 1.375
00 47 3542 ***

TRIANGLE



23"x62" 9/12 Pitch◆

O.D.: 23.1"x 61.8" • Depth: 2.125"
V/A: 89 sq. in. • R/O: 10"x 10"
locking positions: .625, .875, 1.125, 1.375
00 47 0907 ***

23"x56" 10/12 Pitch◆

O.D.: 23.4"x 56" • Depth: 2.125"
V/A: 77 sq. in. • R/O: 9"x 9"
locking positions: .625, .875, 1.125, 1.375
00 47 1007 ***

26"x56" 11/12 Pitch◆

O.D.: 25.8"x 56.3" • Depth: 2.125"
V/A: 96 sq. in. • R/O: 10"x 10"
locking positions: .625, .875, 1.125, 1.375
00 47 1108 ***

26"x52" 12/12 Pitch◆

O.D.: 26"x 52" • Depth: 2.125"
V/A: 88 sq. in. • R/O: 10"x 10"
locking positions: .625, .875, 1.125, 1.375
00 47 1208 ***

17"x34" 12/12 Pitch◆

O.D.: 17"x 34.1" • Depth: 2.125"
V/A: 19 sq. in. • R/O: 4"x 5"
locking positions: .625, .875, 1.125, 1.375
00 47 1204 ***